



EDI ENVIRONMENTAL DYNAMICS INC.  
ATTN: Lyndsay Doetzel  
2195 - 2nd Ave  
Whitehorse YT Y1A 3T8

Date Received: 08-SEP-16  
Report Date: 20-SEP-16 16:25 (MT)  
Version: FINAL

Client Phone: 867-393-4882

## Certificate of Analysis

Lab Work Order #: L1826293  
Project P.O. #: NOT SUBMITTED  
Job Reference: MOUNT NANSEN 16-Y-0089  
C of C Numbers: 1  
Legal Site Desc:

Can Dang  
Senior Account Manager

[This report shall not be reproduced except in full without the written authority of the Laboratory.]

ADDRESS: 8081 Lougheed Hwy, Suite 100, Burnaby, BC V5A 1W9 Canada | Phone: +1 604 253 4188 | Fax: +1 604 253 6700  
ALS CANADA LTD Part of the ALS Group A Campbell Brothers Limited Company

## ALS ENVIRONMENTAL ANALYTICAL REPORT

Grouping	Analyte	Sample ID	Description	Sampled Date	Sampled Time	Client ID
		L1826293-1	Water	07-SEP-16	11:30	WQ-PW
<b>WATER</b>						
<b>Physical Tests</b>	Colour, True (CU)			<5.0		
	Conductivity (uS/cm)			363		
	Hardness (as CaCO3) (mg/L)			187 <sup>HTC</sup>		
	pH (pH)			7.99		
	Total Dissolved Solids (mg/L)			219		
	Turbidity (NTU)			0.24		
<b>Anions and Nutrients</b>	Alkalinity, Total (as CaCO3) (mg/L)			164		
	Chloride (Cl) (mg/L)			<0.50		
	Fluoride (F) (mg/L)			0.100		
	Nitrate (as N) (mg/L)			0.126		
	Nitrite (as N) (mg/L)			<0.0010		
	Sulfate (SO4) (mg/L)			32.1		
<b>Total Metals</b>	Aluminum (Al)-Total (mg/L)			<0.010		
	Antimony (Sb)-Total (mg/L)			<0.00050		
	Arsenic (As)-Total (mg/L)			0.00039		
	Barium (Ba)-Total (mg/L)			0.084		
	Boron (B)-Total (mg/L)			<0.10		
	Cadmium (Cd)-Total (mg/L)			<0.00020		
	Calcium (Ca)-Total (mg/L)			41.6		
	Chromium (Cr)-Total (mg/L)			<0.0020		
	Copper (Cu)-Total (mg/L)			<0.0010		
	Iron (Fe)-Total (mg/L)			<0.030		
	Lead (Pb)-Total (mg/L)			0.00062		
	Magnesium (Mg)-Total (mg/L)			20.2		
	Manganese (Mn)-Total (mg/L)			<0.0020		
	Mercury (Hg)-Total (mg/L)			<0.00020		
	Potassium (K)-Total (mg/L)			0.90		
	Selenium (Se)-Total (mg/L)			<0.0010		
	Sodium (Na)-Total (mg/L)			4.8		
	Uranium (U)-Total (mg/L)			0.00177		
	Zinc (Zn)-Total (mg/L)			<0.050		

\* Please refer to the Reference Information section for an explanation of any qualifiers detected.

## Reference Information

### QC Samples with Qualifiers & Comments:

QC Type Description	Parameter	Qualifier	Applies to Sample Number(s)
Method Blank	Copper (Cu)-Total	MB-LOR	L1826293-1
Matrix Spike	Barium (Ba)-Total	MS-B	L1826293-1
Matrix Spike	Calcium (Ca)-Total	MS-B	L1826293-1
Matrix Spike	Copper (Cu)-Total	MS-B	L1826293-1
Matrix Spike	Magnesium (Mg)-Total	MS-B	L1826293-1
Matrix Spike	Sodium (Na)-Total	MS-B	L1826293-1
Matrix Spike	Nitrate (as N)	MS-B	L1826293-1

### Qualifiers for Individual Parameters Listed:

Qualifier	Description
HTC	Hardness was calculated from Total Ca and/or Mg concentrations and may be biased high (dissolved Ca/Mg results unavailable).
MB-LOR	Method Blank exceeds ALS DQO. Limits of Reporting have been adjusted for samples with positive hits below 5x blank level.
MS-B	Matrix Spike recovery could not be accurately calculated due to high analyte background in sample.

### Test Method References:

ALS Test Code	Matrix	Test Description	Method Reference**
<b>ALK-COL-VA</b>	Water	Alkalinity by Colourimetric (Automated)	EPA 310.2
This analysis is carried out using procedures adapted from EPA Method 310.2 "Alkalinity". Total Alkalinity is determined using the methyl orange colourimetric method.			
<b>CL-IC-N-VA</b>	Water	Chloride in Water by IC	EPA 300.1 (mod)
Inorganic anions are analyzed by Ion Chromatography with conductivity and/or UV detection.			
<b>COLOUR-TRUE-VA</b>	Water	Colour (True) by Spectrometer	BCMOC Colour Single Wavelength
This analysis is carried out using procedures adapted from British Columbia Environmental Manual "Colour- Single Wavelength." Colour (True Colour) is determined by filtering a sample through a 0.45 micron membrane filter followed by analysis of the filtrate using the platinum-cobalt colourimetric method. Colour measurements can be highly pH dependent, and apply to the pH of the sample as received (at time of testing), without pH adjustment. Concurrent measurement of sample pH is recommended.			
<b>EC-PCT-VA</b>	Water	Conductivity (Automated)	APHA 2510 Auto. Conduc.
This analysis is carried out using procedures adapted from APHA Method 2510 "Conductivity". Conductivity is determined using a conductivity electrode.			
<b>F-IC-N-VA</b>	Water	Fluoride in Water by IC	EPA 300.1 (mod)
Inorganic anions are analyzed by Ion Chromatography with conductivity and/or UV detection.			
<b>HARDNESS-CALC-VA</b>	Water	Hardness	APHA 2340B
Hardness (also known as Total Hardness) is calculated from the sum of Calcium and Magnesium concentrations, expressed in CaCO3 equivalents. Dissolved Calcium and Magnesium concentrations are preferentially used for the hardness calculation.			
<b>HG-TOT-CVAFS-VA</b>	Water	Total Hg in Water by CVAFS LOR=50ppt	EPA 1631E (mod)
This analysis is carried out using procedures adapted from "Standard Methods for the Examination of Water and Wastewater" published by the American Public Health Association, and with procedures adapted from "Test Methods for Evaluating Solid Waste" SW-846 published by the United States Environmental Protection Agency (EPA). The procedure involves a cold-oxidation of the acidified sample using bromine monochloride prior to reduction of the sample with stannous chloride. Instrumental analysis is by cold vapour atomic fluorescence spectrophotometry or atomic absorption spectrophotometry (EPA Method 245.7).			
<b>MET-T-CCMS-VA</b>	Water	Total Metals in Water by CRC ICPMS	EPA 200.2/6020A (mod)
Water samples are digested with nitric and hydrochloric acids, and analyzed by CRC ICPMS.  Method Limitation (re: Sulfur): Sulfide and volatile sulfur species may not be recovered by this method.			
<b>NO2-L-IC-N-VA</b>	Water	Nitrite in Water by IC (Low Level)	EPA 300.1 (mod)
Inorganic anions are analyzed by Ion Chromatography with conductivity and/or UV detection.			
<b>NO3-L-IC-N-VA</b>	Water	Nitrate in Water by IC (Low Level)	EPA 300.1 (mod)
Inorganic anions are analyzed by Ion Chromatography with conductivity and/or UV detection.			
<b>PH-PCT-VA</b>	Water	pH by Meter (Automated)	APHA 4500-H "pH Value"
This analysis is carried out using procedures adapted from APHA Method 4500-H "pH Value". The pH is determined in the laboratory using a pH electrode			

## Reference Information

It is recommended that this analysis be conducted in the field.

**PH-PCT-VA** Water pH by Meter (Automated) APHA 4500-H pH Value

This analysis is carried out using procedures adapted from APHA Method 4500-H "pH Value". The pH is determined in the laboratory using a pH electrode

It is recommended that this analysis be conducted in the field.

**SO4-IC-N-VA** Water Sulfate in Water by IC EPA 300.1 (mod)

Inorganic anions are analyzed by Ion Chromatography with conductivity and/or UV detection.

**TDS-VA** Water Total Dissolved Solids by Gravimetric APHA 2540 C - GRAVIMETRIC

This analysis is carried out using procedures adapted from APHA Method 2540 "Solids". Solids are determined gravimetrically. Total Dissolved Solids (TDS) are determined by filtering a sample through a glass fibre filter, TDS is determined by evaporating the filtrate to dryness at 180 degrees celsius.

**TURBIDITY-VA** Water Turbidity by Meter APHA 2130 "Turbidity"

This analysis is carried out using procedures adapted from APHA Method 2130 "Turbidity". Turbidity is determined by the nephelometric method.

**TURBIDITY-VA** Water Turbidity by Meter APHA 2130 Turbidity

This analysis is carried out using procedures adapted from APHA Method 2130 "Turbidity". Turbidity is determined by the nephelometric method.

---

\*\* ALS test methods may incorporate modifications from specified reference methods to improve performance.

---

*The last two letters of the above test code(s) indicate the laboratory that performed analytical analysis for that test. Refer to the list below:*

---

Laboratory Definition Code	Laboratory Location
VA	ALS ENVIRONMENTAL - VANCOUVER, BRITISH COLUMBIA, CANADA

---

### Chain of Custody Numbers:

1

### GLOSSARY OF REPORT TERMS

*Surrogate - A compound that is similar in behaviour to target analyte(s), but that does not occur naturally in environmental samples. For applicable tests, surrogates are added to samples prior to analysis as a check on recovery.*

*mg/kg - milligrams per kilogram based on dry weight of sample.*

*mg/kg wwt - milligrams per kilogram based on wet weight of sample.*

*mg/kg lwt - milligrams per kilogram based on lipid-adjusted weight of sample.*

*mg/L - milligrams per litre.*

*< - Less than.*

*D.L. - The reported Detection Limit, also known as the Limit of Reporting (LOR).*

*N/A - Result not available. Refer to qualifier code and definition for explanation.*

*Test results reported relate only to the samples as received by the laboratory.*

**UNLESS OTHERWISE STATED, ALL SAMPLES WERE RECEIVED IN ACCEPTABLE CONDITION.**

*Analytical results in unsigned test reports with the DRAFT watermark are subject to change, pending final QC review.*

