NATURAL AIR ABSORBED DOSE RATE MAP
CARTE DU TAUX D'EXPOSITION NATUREL

STEWART RIVER AREA
YUKON TERRITORY / TERRITOIRE DU YUKON

Scale 1:50 000 - Echelle 1/50 000

Kilometres 1 0 1 2 3 4 Kilometres

Projection Transverse de Mercator
Universal Transverse Mercator (UTM) Zone 8
Système de référence géodésique nord-américain 1983

Transverse Mercator Projection
North American Datum 1983
© Crown copyright reserved

LOCATION MAP / CARTE DE LOCALISATION



Canada

Natural Resources Canada
Ressources naturelles Canada

Indian and Northern Affairs Canada
Affaires indiennes et du Nord Canada

GEOLOGICAL SURVEY OF CANADA
COMMISSION GÉOLOGIQUE DU CANADA

OPEN FILE
DOSSIER PUBLIC
4308
GEOLOGICAL SURVEY OF CANADA
COMMISSION GÉOLOGIQUE DU CANADA
2002

OPEN FILE
DOSSIER PUBLIC
2002-14
STREAM REPORT AREA
YUKON TERRITORY / TERRITOIRE DU YUKON
EM1,MT/VLF,HEM,MAG,RAD,GEOCHEM,SEDIMENTS
EM1,MT/VLF,HEM,MAG,RAD,GEOCHEM,SEDIMENTS
ARCHIVED NOTE: DIGITAL DATA ARE AVAILABLE FROM GSC OPEN FILE 4308
ARCHIVED NOTE: DIGITAL DATA ARE AVAILABLE FROM GSC OPEN FILE 4308
ARCHIVED NOTE: DIGITAL DATA ARE AVAILABLE FROM GSC OPEN FILE 4308
ARCHIVED NOTE: DIGITAL DATA ARE AVAILABLE FROM GSC OPEN FILE 4308
ARCHIVÉE NOTE: LES DONNÉES NUMÉRIQUES SONT DISPONIBLES DANS LE DOSSIER PUBLIC 4308 DE LA CGC
ARCHIVÉE NOTE: LES DONNÉES NUMÉRIQUES SONT DISPONIBLES DANS LE DOSSIER PUBLIC 4308 DE LA CGC
ARCHIVÉE NOTE: LES DONNÉES NUMÉRIQUES SONT DISPONIBLES DANS LE DOSSIER PUBLIC 4308 DE LA CGC
ARCHIVÉE NOTE: LES DONNÉES NUMÉRIQUES SONT DISPONIBLES DANS LE DOSSIER PUBLIC 4308 DE LA CGC

PUBLISHED 2002 PUBLIÉ 2002







Flight lines, altitude / Lignes de vol, hauteur ..... 2000 ft / pi

Reconnaissance data: Grasty, R.E.K., Lavoie, L.M., Reid, A.L., Holman, P.B., Grasty, S., Kosiuk, G., 2002
Données de reconnaissance : Grasty, R.E.K., Lavoie, L.M., Reid, A.L., Holman, P.B., Grasty, S., Kosiuk, G., 2002
Natural air absorbed dose rate map: Grasty, R.E., Holman, P.B., Grasty, S., Kosiuk, G., 2002
Carte du taux d'exposition naturel : Grasty, R.E., Holman, P.B., Grasty, S., Kosiuk, G., 2002
Base topography: Geological Survey of Canada Open File 4308
Topographie de base : Commission géologique du Canada Dossier public 4308
Stewart River Area - 116O/16
Région de la rivière Stewart - 116O/16
Scale 1:50,000
Échelle 1/50 000

Natural Resources Canada, Geological Survey of Canada, Ottawa, Ontario, 2002
Ressources naturelles Canada, Commission géologique du Canada, Ottawa, Ontario, 2002

The survey was completed from data acquired in the Stewart River Area, Yukon, during the second phase of an airborne geophysical survey carried out by Fugro-Hunting Inc. for the Geological Survey of Canada. Funding for the survey was provided by the Mineral Resources Division, Indian and Northern Affairs Canada. The Phase 2 survey was completed between July 16 and September 26, 2001, using an Aerospatiale AS350B2 helicopter (registration C-GZAL) and Geoterex-Wardrop data acquisition system.

Flight path was recovered using a post-flight differential Global Positioning System. A vertically mounted radio antenna was used for navigation of the flight path. The nominal terrain clearance was 500 m with contour lines down at 2.5 km intervals. Helicopter flight height was maintained at an average ground clearance of 119 m.

The two detectors comprising the gamma ray spectrometer system consisted of 4 L Cesium Iodide (Thallium) crystals (4196 cubic inches) and 1 Cesium Iodide (Thallium) crystal (1049 cubic inches). Cosmic radiation (>3000 keV), uranium (1660 - 1860 keV), potassium (1370 - 1570 keV), total radioactivity (400 - 2810 keV) and ceiling (>3000 keV) were recorded in 256 channels. Data were recorded at 1 second intervals. Aircraft altitude was derived from a GPS receiver and recorded every second. Magnetic field data were recorded from a cesium vapour magnetometer mounted in a towed bird. Data were recorded at 0.1 second intervals. Ambient magnetic field values were recorded every 5 seconds. Magnetic diurnal variations were recorded at 1 second intervals on a base magnetometer operating in a non-magnetic area at the Stewart River Airport. Survey data were recorded digitally on a Geoterex-Wardrop DAS-1000 data acquisition system. Analog data were recorded on a strip chart recorder for visual monitoring purposes.

Survey data were corrected for aircraft and sensor motion, diurnal variations and normal magnetic field. Data were corrected for spatial misalignment, drift and lag. Digital filters were applied to remove cultural noise from the gamma ray spectrometer and magnetometer data. After doing survey data, the measurements of uranium, thorium and potassium were stripped of cosmic and aircraft background components and converted to ground concentrations using calibration coefficients derived from test pad measurements. Radon background components were estimated from upward looking detectors and removed from the data. Ground concentrations were then corrected for water content, using a water correction factor derived from laboratory measurements on soil samples collected during the survey. Corrected data were then normalized to standard concentrations into and ratios and then interpolated to a 125 m square grid. The ternary image grid was created from the three concentration grids.

The magnetometer data were recorded at a 0.1 second sample rate using a 0.01 nT sensitivity system. The overall time constant of the system was 3 seconds. Aircraft manoeuvre and compass deviation corrections were applied to the magnetic field during the data processing. After doing survey data, the measurements of uranium, thorium and potassium were stripped of cosmic and aircraft background components and converted to ground concentrations using calibration coefficients derived from test pad measurements. Radon background components were estimated from upward looking detectors and removed from the data. Ground concentrations were then corrected for water content, using a water correction factor derived from laboratory measurements on soil samples collected during the survey. Corrected data were then normalized to standard concentrations into and ratios and then interpolated to a 125 m square grid. The ternary image grid was created from the three concentration grids.

All gridded data are presented as colour raster maps combined with digital topographic files provided by Geomatics Canada.

Cette carte a été compilée à partir des données obtenues lors la région de Stewart River, Yukon, pendant la deuxième phase d'un levé aéroporté aéroportés géophysique (SCG) de ressources aéroportés pour le compte de la Commission géologique du Canada. Ressources Canada. La deuxième phase d'acquisition des données (SCG) a été effectuée entre le 16 juillet et le 26 septembre, 2001, en utilisant un hélicoptère aérospatiale AS350B2 (immatriculé C-GZAL).

Le positionnement des lignes de vol était fait à l'aide de mesures de système de positionnement global par différentiel (GPS). Une antenne radio montée verticalement a été employée pour la navigation de l'appareil de levé. La hauteur moyenne de vol était de 500 m, disposée sur des lignes de contour espacées d'environ 2,5 km aux mêmes altitudes. La hauteur moyenne de vol était de 119 m.

Les deux détecteurs composant le spectromètre de rayons gamma (un total de 4 cristaux de iodure de césium (thallium) de 4196 pouces cubes et 1 cristal de iodure de césium (thallium) de 1049 pouces cubes) ont enregistré les données de rayonnement cosmique (>3000 keV), uranium (1660 - 1860 keV), thorium (1370 - 1570 keV), le total de radioactivité (400 - 2810 keV) et de rayonnement cosmique (>3000 keV). Les données ont été enregistrées à 1 seconde d'intervalle. L'altitude de l'appareil a été déterminée à partir d'un récepteur GPS et enregistrée à chaque seconde. Les données de champ magnétique ont été enregistrées à l'aide d'un magnétomètre à vapeur de césium monté à l'extérieur d'un oiseau remorqué. Les données ont été enregistrées à des intervalles de 0,1 seconde. Les variations diurnes du champ magnétique ont été enregistrées à des intervalles de 1 seconde à l'aide d'un magnétomètre de référence situé à l'aéroport de Stewart River dans une région non magnétique. Les données ont été enregistrées numériquement à l'aide d'un système d'acquisition de données DAS-1000 de Geoterex-Wardrop. Les données analogiques ont été enregistrées sur un graphique à bande déroulante pour contrôle visuel en temps réel.

Les données ont été corrigées pour les variations de l'altitude et du mouvement de l'appareil, les variations diurnes et le champ magnétique normal. Après avoir effectué les corrections, les mesures de uranium, thorium et potassium ont été dépouillées du rayonnement cosmique et de celui de l'appareil et converties en concentrations au sol à l'aide de coefficients d'étalonnage déterminés à partir des mesures effectuées sur des dalles d'étalonnage. Les composantes du rayonnement de fond dues au radon ont été déterminées à l'aide de détecteurs orientés vers le haut et ont été soustraites des données. Les concentrations au sol ont ensuite été corrigées pour tenir compte de la teneur en eau des échantillons de sol prélevés pendant le levé, à l'aide d'un facteur de correction déterminé à partir de mesures effectuées en laboratoire. Les données ont ensuite été normalisées à des concentrations types et à des rapports, puis interpolées sur un quadrillage régulier de 125 m de côté. Finalement, la grille de la première dérivée verticale du champ magnétique résiduel, obtenue à partir du champ magnétique résiduel, a été calculée à l'aide d'un filtre numérique.

Tous les données ont présentés comme des cartes thématiques en couleurs combinées avec les fichiers de topographie numériques fournis par Géomatique Canada.