

NOTES

Standardization of publicly available digital magnetic data from assessment reports was performed in 2019 and 2020. Residual magnetic field was calculated through removal of the IGRF. A levelled magnetic field channel was calculated by sampling the 1:250 000 compilation grid and taking the mean difference between the residual magnetic field and the overlapping points; this mean difference is applied as zero order datum shift to the residual data. This is repeated for each 1:250 000 compilation that the survey overlaps.

Up to four gridded products are produced for each survey (Residual Total Magnetic Field (TMI), Reduced-to-Pole Magnetic Field (RTP), First Vertical Derivative of the Reduced-to-Pole Magnetic Field (RTP_VD) and Tilt Derivative of the Reduced-to-Pole Magnetic Field (RTP_TDR) and these have pre-existing analogous 1:250 000 products from Open Files 2017-5 to 2017-59.

The outline of the assessment report data is extracted and eroded by a buffer, typically 200 m. The buffer is automatically reduced if it exceeds half the range of either the x or y coordinates. The eroded buffer is then windowed from each of the four corresponding 1:250 000 compilations.

Each assessment report grid is then blended with the compilation grid through averaging common points between the grids. By previously windowing out the eroded assessment report outline from the compilation, both fidelity to the higher quality assessment report data and a smooth transition to avoid edge artifacts are achieved. This is an appropriate approach when the assessment report data are of higher quality than the compilation. Mostly this is true due to the higher resolution of data that is typical of a property-scale survey compared to a government regional-scale survey. However this is not universally the case and for every assessment report each of the four new blended grids are compared with the unaltered compilation. Assessment report grids which upon blending lower the quality of the compilation are manually rejected. A log file of accepted and rejected assessment reports for each 1:250 000 sheet is maintained.

The Yukon Geological Survey created georeferenced *.pdf maps of the shaded relief colour contour products for each 1:250 000 map sheet. The map data are provided as GeoTiff files.

Funding for this project was provided by the Canadian Northern Economic Development Agency through their Strategic Investments in Northern Economic Development program.

REFERENCES

- Miles, W., Saltus, R., Hayward, N. and Oneschuk, D., 2015. Alaska and Yukon Magnetic Compilation, Residual total magnetic field. Geological Survey of Canada, Open File 7862.
- Expatriate Resources Ltd., 1996. Report on a Combined Helicopter-Borne Electromagnetic and Magnetic Survey, Goal Net, Hat Trick, League, Offside, Power Play, Shutout and Slapshot Properties. Yukon Energy, Mines and Resources Assessment Report 93655.
- Expatriate Resources Ltd., 1996. Assessment Report Describing Geological Mapping, Prospecting, Soil Geochemistry, Geophysical Surveys and Diamond Drilling on the Ice Property. Yukon Energy, Mines and Resources Assessment Report 93718.
- Petra Resource Corp., 1999. Horizontal Loop Electromagnetic and Total Magnetic Field Survey at the Starr Property, Ross River Area. Yukon Energy, Mines and Resources Assessment Report 94048.
- Strategic Metals Ltd., 2007. Assessment Report Describing Geophysical Surveys on the Jake Property. Yukon Energy, Mines and Resources Assessment Report 95015.
- Strategic Metals Ltd., 2008. Assessment Report Describing Geological Mapping, Prospecting, Geochemical Sampling and Geophysical Surveys at the Bob Property. Yukon Energy, Mines and Resources Assessment Report 95115.
- 18526 Yukon Inc., 2012. Airborne Geophysical Survey Report on the Expo Block. Yukon Energy, Mines and Resources Assessment Report 96178.
- 18526 Yukon Inc., 2012. Airborne Geophysical Survey Report, Ellen Creek Block. Yukon Energy, Mines and Resources Assessment Report 96179.
- Arcturus Ventures Inc., 2011. Airborne Magnetic Survey on Mer Claims. Yukon Energy, Mines and Resources Assessment Report 96348.



RECOMMENDED CITATION

Aurora Geosciences Ltd. and Bruce, J.O., 2020. Reduced-to-Pole Magnetic Field Shaded Colour Contour Map (NTS 105G). In: Reprocessing of Yukon magnetic data for NTS 105G. Yukon Geological Survey, Open File 2020-15, scale 1:250 000, 4 sheets.


Any revisions or additional geological information known to the user would be welcomed by the Yukon Geological Survey.

Paper copies of this map and the accompanying report may be obtained from the Yukon Geological Survey, Energy, Mines and Resources, Government of Yukon, Room 102-300 Main St., Whitehorse, Yukon, Y1A 2B5. Email: geology@gov.yk.ca.

A digital PDF (Portable Document File) file of this map, and available data, can be downloaded free of charge from the Yukon Geological Survey website: <https://yukon.ca/en/science-and-natural-resources/geology>.




**REDUCED-TO-POLE MAGNETIC FIELD
FINLAYSON LAKE (NTS 105G)
YUKON**



1:250 000-scale topographic base data produced by CENTRE FOR TOPOGRAPHIC INFORMATION, NATURAL RESOURCES CANADA

ONE THOUSAND METRE GRID Universal Transverse Mercator Projection North American Datum 1983 Zone 9



Use diagram only to obtain numerical values APPROXIMATE MEAN DECLINATION 2020 FOR CENTRE OF MAP Annual change 21.5' West

105K TAY RIVER	105J SHELDON LAKE	105I LITTLE NAHANNI RIVER
105F QUIET LAKE	THIS MAP	105H FRANCES LAKE
105C TESLIN	105B WOLF LAKE	105A WATSON LAKE

Yukon Geological Survey
Energy, Mines and Resources
Government of Yukon

Open File 2020-15
Sheet 2 of 4

**Reduced-to-Pole Magnetic Field
Shaded Colour Contour Map (NTS 105G)
(1:250 000 scale)**

by
Aurora Geosciences Ltd.
and
J.O. Bruce